





|   |   |
|---|---|
| REF.  | FA 50 218 60  |
| CE  | EN 362:2004 Class A/T<br>EN 12275 Class K/T   |
|   | 22 kN / 60 mm   |
| MAT.  |  |
|    | DOUBLE ACTION   |
| KEYLOCK   | ---   |
| +   | UIAA / INDIVIDUAL NUMBER  |
|  | 0.45 KG   |



MAT.



**Résistance à la rupture / Ouverture**  
Breaking strength / Gate opening  
**Resistencia a la ruptura / Apertura**  
Resistenza alla rottura / Apertura  
**Bruchfestigkeit / Öffnung**

**Matière**  
Material  
**Material**  
Materia  
**Material**

**Type d'ouverture**  
Opening system  
**Tipo de apertura**  
Sistema di apertura  
**Öffnungssystem**

|  |             |
|--|-------------|
| HS CODE  | 76169990    |
| CARTON SIZE / PCS.   | 39x28x18/25 |
| AET (EU) N°2777/10366-02/E03-01  |             |
| Satra Technology Europe Ltd., N° 2777,<br>Bracetown Business Park, Clonee,<br>Dublin, D15YN2P, Ireland |             |
| MODULE D FI14/14003.02   |             |
| SGS Fimko Oy, N°0598<br>Takomotie 8,<br>00380 HELSINKI, Finland  |             |