










FA 60 012 00

P. 1 | 2



| |
|---|
| HS CODE |
| 73160010 |
| CARTON SIZE / PCS. |
| 40 x 30 x 15 cm / 20 |
| Certificate of Test n°SPC0203799/1218 Issue 2 |
| Satra Technology Centre, N°0321 Wyndham Way, Telford Way, Kettering Northamptonshire, NN16 8SD, United Kingdom |


| | |
|---|--|
| REF. | FA 60 012 00 |
| CE | EN 795:2012 Type A |
|  | X1 |
| MAT. |  |
| R (kN) / MBS (kN) | 12 kN / 23 kN |
|  | Min. 80 80 mm |
|  | 1.05 KG |



Nombre d'utilisateurs
 Number of users
Cantidad de usuarios
 Cantidad de usuarios
Quantità di utilizzatori
 Quantità di utilizzatori
Anzahl der Benutzer
 Anzahl der Benutzer

R (kN) / MBS (kN)

Résistance statique (en kN) / Résistance à la rupture
 Static strength / Minimum Breaking Strength
Resistencia estática (en kN) / Resistencia a la ruptura (en kN)
 Resistencia estática (in kN) / Resistencia a la ruptura (in kN)
Statische Festigkeit (in kN) / Bruchfestigkeit (in kN)



Fixations à utiliser / Dimensions de la structure d'accueil
 Fasteners to use / Dimensions of the receiving structure
Fijaciones que deben usarse / Dimensiones de la estructura receptora
 Elements of fastening to use / Dimensions of the receiving structure
Zu verwendende Befestigungen / Abmessungen der Aufnahmestruktur